

Automatic Rotary Capper

Model No.: CR-210



It is a complete capping system which includes the cap bulk supply, cap orienting and delivery, cap placement and tightening, and container ingress, staging and discharge onto the customer-supplied existing conveyor.

FEATURES:

- Frame and component made of SUS#304 and ion anodized aluminum, all meet cGMP requirement
- Heavy-duty conveyor by MCC slat top-chain
- No bottle, no cap
- Sophisticated capping module
- Torque capping mechanism ensure no over-capping
- Precise wire cutting capping head, fit to cap with perfection
- Vibratory cap orientation with reject system
- Interchangeable star wheel for different diameter of bottle

OPTIONS:

- Bottle infeed and outfeed accumulation tray
- Customized star wheel for bottle position
- Door-open auto-stop comply with safety operation
- Turnkey linkage with capper, labeler and other in-line systems

SPECIFICATIONS:

- Power : 110/220VAC, 50/60Hz
- Suit for plastic screw or press cap
- Capping speed : 30-40 Bottles/min
- Works with caps from 22mm to 120mm in diameter
- Air requirement : 6kgf/cm²
- Dimension : (L)2500mm(W)1200 mm(H) 1600mm

DOWNLOAD:



The above specifications are subject to change without prior notice.