

High Speed Rotary Capping Machine

Model No.: *CR-415S*



High Speed Rotary Capping Machine CR-415S is versatile monobloc starwheel based, fully automatic capping machine which can be customised to suit the application. It can be integrated into an existing line or supplied as a self contained unit with in-feed, out-feed systems and conveyors with options for filling, plugging, capping and many other features.

FEATURES:

- Servo motor torque capping heads control torque digitally
- PLC Control system combined with HMI(touch screen)
- Automatic Cap elevator, feed and place cap at once
- Digital output torque adjustment
- Emergency stop and Three -color indicate light
- Continuous capping 「No Bottle, No Cap」 Design
- Heavy-duty conveyor by MCC slat top-chain
- Linear Cutting capping head to ensure
- Quick swap change parts
- 20 slots memory recall
- Frame and component made of SUS#304 and ion anodized aluminum, all meet cGMP requirement
- Water-proof with IP54 grade
- Safety interlocks with clear acrylic guard, auto-stop when door is open

OPTIONS:

- Low cap supply sensor and alarms
- Alarm for miss-aligned or missing caps
- Bottle infeed and outfeed system
- Customized star wheel and capping head
- Turnkey linkage with filler, labeler and other in-line systems

SPECIFICATIONS:

Cap type: Screw and press cap (Customized cutting)

Standard Cap Size: 25mm – 60mm O.D.

Capping Speed: 30~40 Bottles/min

Air Requirements: 90 PSI @ 3 CFM6Kg

Power: single phase 110/220VAC, 50/60Hz

 Machine Dimension: (L)2758mm (W)1237mm (H)1800mm (For reference only, the real drawing should be considered as final.)

The above specifications are subject to change without prior notice.

Industry | Automation | Labeler | Coder | Filler | Capper | Tablet Counter

No.15, Ln. 316, Guangxing Rd., Bade Dist, Taoyuan City 334, Taiwan (R.O.C.)

Tel: +886-3-3689806 Fax: +886-3-3689807 sales@autopacker.com

All Rights Reserved $\ensuremath{\mathbb{C}}$ AutoPack Co., Ltd.