

Tabletop Peristaltic Pump Liquid Filler

Model No.: *FT-100*

It is the best system to avoid contamination, product is only in contact with the medically approved tubing and the nozzle, against cross contamination and easy cleaning. Without having to change anything but the dimension of the tubing in use. The target market is small to medium-sized batch production that requires flexibility, high precision and efficiency.

FEATURES:

- Easy to set, even if the novice can also with ease
- With peristaltic pump, product is only in contact with the tubing
- Made of SUS 316 and 316L stainless steel, meets cGMP requirement
- LED display, easy adjusting filling volume, speed and between filling
- Draws liquids directly from a tank or drum, or add a hopper if need
- Without any change parts other than tubing
- Three operating modes: manual, intermittent filling or foot switch
- Three kind of filling velocities are available
- Apply liquid like water, eye drops, lotion, hot sauce (under 60°C) or any other free flowing liquid

OPTIONS:

- 3.5L stainless steel tank
- Heater (under 140°F/ 60°C)
- Diving nozzle with bracket
- Foot switch
- Photocell activation
- Vacuum nozzle

SPECIFICATIONS:

- Power : 110/220VAC, 50/60Hz
- Filling Range : 5~500ml
- Filling Speed : 5~50ml/sec
- Accuracy : 0.5%~1%
- Dimension : (L)360mm(W)580mm (H)325mm

DOWNLOAD:

The above specifications are subject to change without prior notice.