



Top Tamp Labeling Machine

Model No.: **LS-450**



Top Tamp Labeling Machine LS-450 is ideal for labeling recessed areas and irregular shape items that demand precise label placement.

FEATURES:

- Labeling accuracy: $\pm 0.5\text{mm}$
- The tamp pad guarantee NO Bubble labeling
- PLC Program. The HMI touch screen Input
- 50 job set-ups job memory for recall
- Stand alone on a high-end floor stand with caster wheels,
- Double guided stem pneumatic cylinder ensures precise delivery of the label in a consistent fashion
- Pressing label unit will get label well attached
- Through Beam Optic Fiber Sensation System to get perfect product Positioning
- Simple Adjustment of labeling head by Hand Wheel with Position Indicator
- Customized placement for product orientation
- Activated by Foot Pad or Photocell

OPTIONS:

- Hot Stamping Coding Machine(PE-200,PM-200)/Ink jet printer
- LION Clear Label Sensor
- Stainless cabinet type
- Accumulation tray

SPECIFICATIONS:

- Labeling Speed: 20-40 bottles/ min (Depends on Manual infeed speed)
- Product Size: Diameter 20mm-125mm / Height 30-160mm
- Label Width: 10- 60mm
- Label Length: 10-60 mm
- Label Roll: Inner diameter 75mm / Outer Diameter 300mm
- Power: single phase 110/220VAC, 50/60Hz
- Air consumption: 2.3 cfm at 50 psi
- Machine Dimensions: (L)591mm (W)746mm (H)1068mm
(For reference only, the real drawing should be considered as final.)

The above specifications are subject to change without prior notice.

Industry | Automation | Labeler | Coder | Filler | Capper | Tablet Counter

No.15, Ln. 316, Guangxing Rd., Bade Dist, Taoyuan City 334, Taiwan (R.O.C.)

Tel: +886-3-3689806 Fax: +886-3-3689807 sales@autopacker.com

All Rights Reserved © AutoPack Co., Ltd.